

THE GUARDIAN.

Today's evolving operations call for advanced sand control & monitoring solutions in production & flowback.

Sandtinel® offers solutions that are highly effective, simple, safe, & versatile that also reduce environmental impacts.

Thriving in extreme conditions, Sandtinel's Guardian 10k unit is powerful & adaptable, defending in high pressure well conditions.

DON'T HOLD YOUR WELL BACK

KEY SPECIFICATIONS

MAWP PSI

M10-G4-S2

10,000_{psi}

PRODUCTION UP TO

13,000 BPD @ 15 MMSCFD

INTERIOR DIAMETER (ID)

44"

EFFICIENT STORAGE

150 - 400lbs

CAPTURE RATE

95+%

VL-TEK VAPOR LOCK

1

FILTER-LESS

/

APPLICATION









OPTIMIZING FLOWBACK

95%+ SAND REMOVAL

50% LESS EQUIPMENT

55x LOWER EMISSIONS*


20% MORE PRODUCTION**

ELIMINATE CHARGEBACKS

BOOK A DEMO: (833) 539-7263

THE SCIENCE OF SAND

SANDTINEL OPERATING CURVES: 44" GUARDIAN 10k



THE SANDTINEL ADVANTAGE

CFD Modeling & Analysis


Enhanced Data & Reporting

Engineering & Field Support

Tailored Proposals & Features

Global Reach with Local Service

DRAIN CYCLE EMISSIONS COMPARISONS SANDTINEL vs. Cyclonic Cyclonic (Gas) Cyclonic (Water) Cyclonic (Water) Sandtinel (2/SCF)



Sand Dump Time (s)